# GLORY

## WITH DECORATIVE FRONT PANEL AND LIGHTING

## Features

- Wall mounting
- Easy maintenance
- Low-noise impeller
- Continuous operation
- Ball bearing motor
- Glass front cover
- Built-in 2 W LED-lamp
- 5 year warranty

**Air flow:**
up to 258 m³/h
72 l/s

**Power:**
from 14 W

**SFP:**
from 0.33 W/l/s

**Noise level:**
from 33 dBA




## Options

| Model | Glory 100/125/150 | |
|---|---|---|
| Option | T | H |
| Timer | • | • |
| Humidity sensor | | • |

- Turn-off delay adjustable from 2 to 30 min.
- Humidity setpoint adjustable from 60 % up to 90 %.

## Overall dimensions





| Dimensions [mm] | a | b | c | Ø D | e |
|---|---|---|---|---|---|
| Glory 100 | 180 | 120 | 143 | 100 | 49 |
| Glory 100 T | 183 | 122 | 151.6 | 98 | 65 |
| Glory 100 H | 183 | 122 | 151.6 | 98 | 65 |
| Glory 125 | 204 | 140 | 152 | 125 | 55 |
| Glory 150 | 230 | 165 | 169 | 150 | 53 |

| Designation key | | | |
|---|---|---|---|
| Glory | - 1 | 125 | H |
| Model | Decorative panel | Spigot diameter | Option |

## Technical data

| Model | Glory 100 | Glory 125 | Glory 150 |
|---|---|---|---|
| Voltage [V/Hz] | 220-240/50 | 220-240/50 | 220-240/50 |
| Power [W] | 14 | 16 | 24 |
| Current [A] | 0.085 | 0.1 | 0.13 |
| RPM [min⁻¹] | 2300 | 2400 | 2400 |
| Air flow [m³/h (l/s)] | 89 (25) | 164 (46) | 258 (72) |
| SFP [W/l/s] | 0.57 | 0.35 | 0.33 |
| Noise level [dBA] | 33 | 34 | 37 |




IP24

## Decorative panels


Glory - 1


Glory - 2


Glory - 3


Glory - 4


Glory - 5


Glory - 6

## Accessories

| Duct system | Flexible air ducts | Grilles and hoods | | | Speed controllers | | Clamps |
|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| BlauPlast | BlauFlex | Decor, GM | | | CDT E1.8 | MCD 60/0.3 | K, KZ |