

CEILEO COMPACT

CENTRIFUGAL FANS

Low profile exhaust fans with low noise and power consumption for ceiling mounting



Air flow:
up to 270 m³/h
75 l/s



Power:
from 20 W

SFP:
from 0.49 W/l/s



Noise level:
from 24 dBA



Features



- Intermittent or continuous ventilation of bathrooms, showers, kitchens and other domestic spaces.
- For high-resistant ventilation systems.
- Integrated LED light with low energy demand (**Ceileo Compact Light** models).
- The modular design enables easy connection of the optional humidity or motion sensors (not accessible for the basic model) or the grille with a LED light.
- Constant air flow.
- Low noise level.
- The centrifugal impeller has forward curved blades for high pressure and low noise.
- The fan's impeller is made of high-quality durable ABS plastic.
- The fans also are equipped with a gravity backdraft damper.
- Ingress protection rating IPX2.
- Compatible with Ø 100 mm air ducts.

Motor

- The **Ceileo Compact** fans are equipped with reliable asynchronous two-speed motors with overheating protection.
- The maintenance-free permanently lubricated motor bearings are engineered for over 40 000 operating hours of trouble-free operation.

Design

- The casing is made of galvanized steel.
- The clip-on plastic grille ensures easy mounting and cleaning of the fan.
- The modular design of the grille enables easy retrofitting with the optional humidity or motion sensors.



- **Ceileo Compact Light** fans are equipped with an energy efficient LED light.

Power: 10 W
Colour temperature:
3 000 K
Luminous flux:
650 lumens




Power: 60 W

Plastic grille with LED light
(Ceileo Compact Light)

Plastic grille
(Ceileo Compact)



Assembled fan



Mounting bracket

Casing


CEILEO COMPACT

CENTRIFUGAL FANS


Options

Ceileo Compact: Double-speed basic fan model.

Ceileo Compact T: Models with an adjustable turn-on and turn-off delay timer. This model can also be retrofitted with an optional humidity or motion sensor (available on a special order basis).



Humidity sensor



Motion sensor

Control

The built-in control panel of the **Ceileo Compact T** fans enables the following settings:

- turn-on delay by timer
- turn-off delay by timer
- humidity level
- air flow for the operating modes 1 and 2

Name	Adjustment range for operation modes 1 and 2
Ceileo Compact 200 T	Off / Speed 1/Speed 2
Ceileo Compact 250 T	Off / Speed 1/Speed 2

Ceileo Compact T control panel



MANUAL CONTROL

The fan is controlled by means of the CDP-2/10 speed switch (available as a specially ordered accessory).



AUTOMATIC CONTROL



Timer: The fan is continuously running in the mode 1. Upon the light switch closing, the fan goes to mode 2 after the turn-on delay timer countdown (from 0 to 3 minutes). Upon the light switch is turned off the built-in turn-off delay timer keeps the fan running in the mode 2 from 1 to 90 minutes. On elapsing of this period the fan reverts to the mode 1.





Timer and humidity sensor (available as a specially ordered accessory): the fan runs continuously in the mode 1. If the indoor humidity level exceeds the sensor threshold value set in the 50-90 % range, the fan switches to the mode 2. When the humidity level reverts to the pre-set value, the built-in turn-off delay timer keeps the fan running in the mode 2 from 1 to 90 minutes. On elapsing of this period the fan reverts to the mode 1.



Timer and motion sensor (available as a specially ordered accessory): the fan runs continuously in the mode 1. If the motion sensor detects movement within its operation zone, the fan goes to the mode 2. When the movement is no longer registered, the built-in turn-off delay timer keeps the fan running in the mode 2 from 1 to 90 minutes. On elapsing of this period the fan reverts to the mode 1.

Overall dimensions



Dimensions [mm]	Ø d	L1	L2	A	B	C	E	H	h	G
Ceileo Compact 200/250	98	100	40.5	330	278	255	395	134	18	max 620
Ceileo Compact 200/250 Light	98	100	40.5	330	278	255	395	134	57	max 620

Mounting

- The fan is integrated into ceiling spaces.
- The fan is attached to the ceiling joists with a mounting bracket and self-tapping screws.
- The flexible air duct is attached to the fan exhaust spigot with a fixing clamp.
- Reduced casing height allows installing fans in ceilings with a thickness from 140 mm.



Designation key

Ceileo Compact	200	Light	T
Series	Rated air flow [CFM]	LED-lamp available	Option

CEILEO COMPACT

CENTRIFUGAL FANS



Technical data

Model	Ceileo Compact 200 (Light) Ceileo Compact 200 (Light) T				Ceileo Compact 250 (Light) Ceileo Compact 250 (Light) T			
	min	max	min	max	min	max	min	max
Voltage [V/Hz]	220-240/50		220-240/60		220-240/50		220-240/60	
Power [W]	20	29	21	34	23	39	25	50
LED-light power [W]**	2 × 10				2 × 10			
RPM [min ⁻¹]	714	1026	588	936	756	1122	732	1140
Current [A]	0.1	0.13	0.11	0.15	0.12	0.18	0.14	0.22
Air flow [m ³ /h (l/s)]	130 (36)	210 (58)	130 (36)	225 (63)	170 (47)	260 (72)	160 (44)	270 (75)
SFP [W/l/s]	0.55	0.50	0.58	0.54	0.49	0.54	0.56	0.67
Sound pressure level [dBA]*	24	27	24	28	25	29	25	30
Weight [kg]	5.3 (6.4**)				5.3 (6.4**)			
Ingress protection	IPX2				IPX2			
SEC class***	C				C			

* Sound pressure level measured in free space at a distance of 3 meters from the fan.

** Only for the Light model

*** For fans with humidity or motion sensors



ENERG Y UA
 енергия · ενεργεια IE IA

BLAUBERG Ceileo Compact 250 H

A+

A

B

C

D

E

F

G

C

48
dB









120 m³/h

ENERGIJA · ΕΝΕΡΓΙΑ · ENERGIJA · ENERGIJA · ENERGIJA · ENERGIJA · ENERGIJA
 2021 1254/2014

CEILEO COMPACT

CENTRIFUGAL FANS

Accessories

Accessory name	Description	Ceileo Compact 200 (Light) Ceileo Compact 250 (Light)	Ceileo Compact 200 (Light) T Ceileo Compact 250 (Light) T
CDP-2/10	 Speed switch	•	•
HS Ceileo	 Humidity sensor		•
IRS Ceileo	 Motion sensor		•
Decor S 102 HK	 Stainless steel outer ventilation hood Ø 100 mm	•	•
Decor 155x155/100H	 Outer ventilation hood Ø 100 mm	•	•
BlauFlex PVC/102/3	 Flexible air duct Ø 100 mm, 3 m long	•	•
K 100	 Quick-detachable stainless steel clamp Ø 90-110 mm	•	•
CH-PLC-10WG23	 10 W LED-light with colour temperature 3000 K (only for the Light models)	•	•