AERO STILL

SILENT & ENERGY SAVING

Features

- Wall and ceiling mounting
- Low energy consumption and noise
- Easy maintenance
- Continuous operation
- Backdraft damper
- Ball bearing motor
- Available in chrome (Aero Chrome) and gold (Aero Gold) decorations
- 5 year warranty

Air flow:
up to 254 m³/h
71 l/s

Power:
from 5.5 W

SFP:
from 0.21 W/l/s

Noise level:
from 25 dBA




Gold


Chrome


Vintage


Options

Model	Aero Still 100/125/150				
Option	S	T	ST	H	SH
Pull-cord switch	•		•		•
Timer		•	•	•	•
Humidity sensor				•	•

- Turn-off delay adjustable from 2 to 30 min.
- Humidity setpoint adjustable from 60 % up to 90 %.


Technical data

Model	Aero Still 100	Aero Still 125	Aero Still 150
Voltage [V/Hz]	220-240/50	220-240/50	220-240/50
Power [W]	5.5	9.4	19
Current [A]	0.035	0.059	0.14
Air flow [m³/h (l/s)]	84 (23)	158 (44)	254 (71)
SFP [W/l/s]	0.24	0.21	0.27
Noise level [dBA]	25	31	33





IP34

Overall dimensions and mounting



Dimensions [mm]	a	b	c	Ø d	e
Aero Still 100	144	122	92.5	100	29.5
Aero Still 125	168	144	97	125	30
Aero Still 150	198	170	119	150	30





Designation key

Aero	Still	Gold	125	SH
Model	Silent	Color	Spigot diameter	Option

Accessories

Duct system	Flexible air ducts	Grilles and hoods	Speed controllers	Clamps
				
BlauPlast	BlauFlex	Decor, GM	CDT E1.8 / MCD 60/0.3	K, KZ