

| | | | | | | |
|---|----------------------|----|---------|----|-------|---|
| Trade mark | BLAUBERG | | | | | |
| Model | KOMFORT EC SB350 S14 | | | | | |
| Specific energy consumption (SEC), kWh/(m ² .a) | Cold | | Average | | Warm | |
| | -80,4 | A+ | -42,1 | A+ | -17,5 | E |
| Type of ventilation unit | Bidirectional | | | | | |
| Type of drive installed | Variable speed | | | | | |
| Type of heat recovery system | Recuperative | | | | | |
| Thermal efficiency of heat recovery, % | 84 | | | | | |
| Maximum flow rate, m ³ /h | 375 | | | | | |
| Electric power input, W | 166 | | | | | |
| Sound power level, dB(A) | 49 | | | | | |
| Reference flow rate, m ³ /s | 0,073 | | | | | |
| Reference pressure difference, Pa | 50 | | | | | |
| Specific power input (SPI), W/(m ³ /h) | 0,24 | | | | | |
| Control typology | Local demand control | | | | | |
| Maximum internal leakage rates, % | 2,7 | | | | | |
| Maximum external leakage rates, % | 2,7 | | | | | |
| Internet address | | | | | | |
| The annual electricity consumption (AEC), kWh electricity/a | Cold | | Average | | Warm | |
| | 709 | | 172 | | 127 | |
| The annual heating saved (AHS), kWh primary energy/a | Cold | | Average | | Warm | |
| | 8 938 | | 4 569 | | 2 066 | |