

Trade mark	BLAUBERG					
Model	VENTO Ergo A85 S Pro1					
Specific energy consumption (SEC), kWh/(m ² .a)	Cold		Average		Warm	
	-83,2	A+	-40	A	-14,9	E
Type of ventilation unit	Bidirectional					
Type of drive installed	Multi-speed					
Type of heat recovery system	Regenerative					
Thermal efficiency of heat recovery, %	90					
Maximum flow rate, m ³ /h	43					
Electric power input, W	5					
Sound power level, dB(A)	40					
Reference flow rate, m ³ /s	0,004					
Reference pressure difference, Pa	N/A					
Specific power input (SPI), W/(m ³ /h)	0,283					
Control typology	Local demand control					
Maximum internal leakage rates, %	N/A					
Maximum external leakage rates, %	N/A					
Mixing rate of bidirectional units, %	1					
Airflow sensitivity at +20 Pa and -20 Pa	0,58					
The indoor/outdoor air tightness, m ³ /h	0,5					
Internet address	http://www.blaubergventilatoren.de/					
The annual electricity consumption (AEC), kWh electricity/a	Cold	Average		Warm		
	197	197		197		
The annual heating saved (AHS), kWh primary energy/a	Cold	Average		Warm		
	8 647	4 420		1 999		