





Fittings for round air ducts

■ Clamp for round flexible ducts K

- Made of galvanized steel
- Mounting of flexible air ducts

	Model	Diameter (d)	Band width (b)	
	K 100	90-110 mm	9 mm	
	K 125	110-130 mm	9 mm	
	K 150	140-160 mm	9 mm	
	K 160	150-170 mm	9 mm	
	K 200	190-210 mm	9 mm	



■ Clamp for round ducts KZ

- Made of galvanized steel with microporous rubber for vibration damping
- Mounting of round air ducts
- Wall or ceiling mounting

	Model	Diameter (d)	Height (h)	
	KZ 80	80 mm	152 mm	
	KZ 100	100 mm	172 mm	
	KZ 125	125 mm	198 mm	
	KZ 150	150 mm	224 mm	
	KZ 160	160 mm	232 mm	
	KZ 200	200 mm	274 mm	
	KZ 250	250 mm	326 mm	
KZ 315	315 mm	380 mm		
	Model	Diameter (d)	Height (h)	
	KZH 80	80 mm	94 mm	
	KZH 100	100 mm	204 mm	
	KZH 125	125 mm	229 mm	
	KZH 150	150 mm	254 mm	
	KZH 160	160 mm	264 mm	
	KZH 200	200 mm	304 mm	
	KZH 250	250 mm	354 mm	
KZH 315	315 mm	419 mm		



■ Flange for round ducts AP

- Made of white polysterene
- Connection of round flexible air ducts
- Wall or ceiling mounting with screws
- Equipped with a lock ring for fixation of flexible air ducts

	Model	Diameter (d)	Diameter (d1)	Length (l)	
	AP 80	80 mm	115 mm	62 mm	
	AP 100	100 mm	132 mm	62 mm	
	AP 125	125 mm	157 mm	62 mm	
	AP 150	150 mm	179 mm	62 mm	
	AP 200	200 mm	232 mm	62 mm	




■ Flange for round ducts FR

- Made of white polymer coated steel (**FRM**) or galvanized steel (**FRZ**)
- Connection of round flexible air ducts
- Wall or ceiling mounting with screws

	Model	Diameter (d1)	Diameter (d2)	Length (l)	
	FRM 80	80 mm	116 mm	62 mm	
	FRM 100	100 mm	136 mm	62 mm	
	FRM 125	125 mm	162 mm	62 mm	
	FRM 150	150 mm	186 mm	62 mm	
	FRM 160	160 mm	196 mm	62 mm	
	FRM 200	200 mm	236 mm	62 mm	
	FRM 250	250 mm	286 mm	62 mm	
	FRM 315	315 mm	351 mm	62 mm	
	FRZ 80	80 mm	116 mm	62 mm	
	FRZ 100	100 mm	136 mm	62 mm	
	FRZ125	125 mm	162 mm	62 mm	
	FRZ150	150 mm	186 mm	62 mm	
	FRZ160	160 mm	196 mm	62 mm	
	FRZ200	200 mm	236 mm	62 mm	
	FRZ250	250 mm	286 mm	62 mm	
	FRZ315	315 mm	351 mm	62 mm	


■ Round duct reducer RS

- Made of white polymer coated steel (**RSM**) or galvanized steel (**RSZ**)
- For connection of round air ducts

	Model	Diameter (d1)	Diameter (d2)	Length (l)	
	RSM 80/100	80 mm	100 mm	115 mm	
	RSM 100/125	100 mm	125 mm	125 mm	
	RSM 100/150	100 mm	150 mm	125 mm	
	RSM 125/150	125 mm	150 mm	125 mm	
	RSM 125/160	125 mm	160 mm	144 mm	
	RSM 150/160	150 mm	160 mm	172 mm	
	RSM 160/200	160 mm	200 mm	154 mm	
	RSM 150/200	150 mm	200 mm	172 mm	
	RSM 200/250	200 mm	250 mm	172 mm	
	RSM 250/315	250 mm	315 mm	195 mm	
	RSZ 80/100	80 mm	100 mm	115 mm	
	RSZ 100/125	100 mm	125 mm	125 mm	
	RSZ 100/150	100 mm	150 mm	125 mm	
	RSZ 125/150	125 mm	150 mm	125 mm	
	RSZ 125/160	125 mm	160 mm	144 mm	
	RSZ 150/160	150 mm	160 mm	172 mm	
	RSZ 160/200	160 mm	200 mm	154 mm	
	RSZ 150/200	150 mm	200 mm	172 mm	
	RSZ 200/250	200 mm	250 mm	172 mm	
	RSZ 250/315	250 mm	315 mm	195 mm	

■ Cross joint for round duct KS

- Made of white polymer coated steel (**KSM**) or galvanized steel (**KSZ**)
- Connection of round air ducts

	Model	Diameter (d)	Length (l)	
	KSM 80	80 mm	170 mm	
	KSM 100	100 mm	190 mm	
	KSM 125	125 mm	215 mm	
	KSM 150	150 mm	240 mm	
	KSM 160	160 mm	250 mm	
	KSM 200	200 mm	300 mm	
	KSM 250	250 mm	350 mm	
	KSM 315	315 mm	415 mm	
	KSZ 80	80 mm	170 mm	
	KSZ 100	100 mm	190 mm	
	KSZ 125	125 mm	215 mm	
	KSZ 150	150 mm	240 mm	
	KSZ 160	160 mm	250 mm	
	KSZ 200	200 mm	300 mm	
	KSZ 250	250 mm	350 mm	
	KSZ 315	315 mm	415 mm	



■ **T-connector for round air ducts TS-90°**

- Made of white polymer coated steel (**TSM**) or galvanized steel (**TSZ**)
- Connection of round air ducts

	Model	Diameter (d)	Length (l)		
	TSM-90° 80	80 mm	170 mm		
	TSM-90° 100	100 mm	190 mm		
	TSM-90° 125	125 mm	215 mm		
	TSM-90° 150	150 mm	240 mm		
	TSM-90° 160	160 mm	250 mm		
	TSM-90° 200	200 mm	300 mm		
	TSM-90° 250	250 mm	350 mm		
	TSM-90° 315	315 mm	415 mm		
	TSZ-90° 80	80 mm	170 mm		
	TSZ-90° 100	100 mm	190 mm		
	TSZ-90° 125	125 mm	215 mm		
	TSZ-90° 150	150 mm	240 mm		
	TSZ-90° 160	160 mm	250 mm		
	TSZ-90° 200	200 mm	300 mm		
TSZ-90° 250	250 mm	350 mm			
TSZ-90° 315	315 mm	415 mm			

■ **T-connector for round ducts TS-120°**

- Made of white polymer coated steel (**TSM**) or galvanized steel (**TSZ**)
- Connection of round air ducts

	Model	Diameter (d)	Height (h)		
	TSM-120° 80	80 mm	170 mm		
	TSM-120° 100	100 mm	190 mm		
	TSM-120° 125	125 mm	200 mm		
	TSM-120° 150	150 mm	240 mm		
	TSM-120° 160	160 mm	250 mm		
	TSM-120° 200	200 mm	300 mm		
	TSM-120° 250	250 mm	350 mm		
	TSM-120° 315	315 mm	415 mm		
	TSZ-120° 80	80 mm	170 mm		
	TSZ-120° 100	100 mm	190 mm		
	TSZ-120° 125	125 mm	200 mm		
	TSZ-120° 150	150 mm	240 mm		
	TSZ-120° 160	160 mm	250 mm		
	TSZ-120° 200	200 mm	300 mm		
TSZ-120° 250	250 mm	350 mm			
TSZ-120° 315	315 mm	415 mm			



■ Flange with a plate for round ducts FQ

- Made of white polymer coated steel (FQM) or galvanized steel (FQZ)
- Mounting with round air ducts
- Wall or ceiling mounting with screws

 	Model	Diameter (d)	Overall dimensions (a)	Mounting dimensions (b)	Length (l)	
	FQM 80	80 mm	130 x 130 mm	114 x 114 mm	50 mm	
	FQM 100	100 mm	150 x 150 mm	134 x 134 mm	50 mm	
	FQM 125	125 mm	170 x 170 mm	156 x 156 mm	50 mm	
	FQM 150	150 mm	204 x 204 mm	188 x 188 mm	50 mm	
	FQM 160	160 mm	210 x 210 mm	194 x 194 mm	50 mm	
	FQM 200	200 mm	250 x 250 mm	234 x 234 mm	50 mm	
	FQM 250	250 mm	300 x 300 mm	284 x 284 mm	50 mm	
	FQM 315	315 mm	360 x 360 mm	344 x 344 mm	50 mm	
	FQZ 80	80 mm	130 x 130 mm	114 x 114 mm	50 mm	
	FQZ 100	100 mm	150 x 150 mm	134 x 134 mm	50 mm	
	FQZ 125	125 mm	170 x 170 mm	156 x 156 mm	50 mm	
	FQZ 150	150 mm	204 x 204 mm	188 x 188 mm	50 mm	
	FQZ 160	160 mm	210 x 210 mm	194 x 194 mm	50 mm	
	FQZ 200	200 mm	250 x 250 mm	234 x 234 mm	50 mm	
	FQZ 250	250 mm	300 x 300 mm	284 x 284 mm	50 mm	
FQZ 315	315 mm	360 x 360 mm	344 x 344 mm	50 mm		

■ Backdraft damper for round ducts VRV

- Galvanized steel body and aluminium blades
- For prevention of back drafting in round air ducts
- Damper blades are opened by pressure and closed with a spring
- Connection to round air ducts by clamps

	Model	Diameter (d)	Length (l)	
	VRV 100	99 mm	80 mm	
	VRV 125	124 mm	100 mm	
	VRV 150	149 mm	115 mm	
	VRV 160	159 mm	120 mm	
	VRV 200	199 mm	145 mm	
	VRV 250	249 mm	165 mm	
	VRV 315	314 mm	190 mm	

■ **Round duct connector SV**

- Made of white polymer coated steel (**SVM**) or galvanized steel (**SVZ**)
- Connection of round air ducts

	Model	Diameter (d)	Length (l)	
	SVM 80	80 mm	62 mm	
	SVM 100	100 mm	62 mm	
	SVM 125	125 mm	62 mm	
	SVM 150	150 mm	62 mm	
	SVM 160	160 mm	62 mm	
	SVM 200	200 mm	62 mm	
	SVM 250	250 mm	62 mm	
	SVM 315	315 mm	62 mm	
	SVZ 80	80 mm	62 mm	
	SVZ 100	100 mm	62 mm	
	SVZ 125	125 mm	62 mm	
	SVZ 150	150 mm	62 mm	
	SVZ 160	160 mm	62 mm	
	SVZ 200	200 mm	62 mm	
	SVZ 250	250 mm	62 mm	
	SVZ 315	315 mm	62 mm	